

Impressed Current Anode (ICCP)



Betelguard Flex Linear Anode (Ti Wire Anode)



Carbon pre-packaged **Betelguard Flex Linear MMO Titanium Wire Anode** for the underground application can be installed without the need of additional carbon backfill.

High-performance Flex Linear Anode is light weight and long life due to the highest quality MMO coating in the industry.

Specification

Type	FL15	FL30
Anode	MMO Ti wire (1.5 mm dia.)	MMO Ti wire (3.0 mm dia.)
Outer Diameter	38 mm (1.5 inch)	38 mm (1.5 inch)
Current Output	328 mA/m (100 mA/ft)	656 mA/m (200 mA/ft)
Expected Life	Greater than 40 years	Greater than 40 years
Cable Size	No. 6 or No. 8 AWG	No. 6 or No. 8 AWG
Cable Insulation	XLPE/PVC, HMWPE, Kynar, or Halar, as specified	XLPE/PVC, HMWPE, Kynar, or Halar, as specified
Coke Breeze	Fixed carbon > 98.3%	Fixed carbon > 98.3%
Minimum Bending Radius	500 mm (6 inches)	500 mm (6 inches)

Packaging

Length per Roll: 500 m, 700 m or 1,000 m (1,640 ft, 2,300 ft, 3,280 ft)

Weight: Approx. 1.5 kg/m (1 lb/ft)

Other sizes are available upon request.

