

Power Self-Healing Concrete Crack Repair



Power Healing L300, L400 & L500 for Oil Mixed Water Leakage Cracks

Transparency
Liquid

Super
Durability

Simple
Application

100%
Inorganic



The combination of **Power Healing L300, L400, and L500** is designed to seal the water-oil mixed leaking cracks (less than 0.3 mm). Only these products can repair the cracks when the leaking water contains oil.

It is so quick to seal the cracks and does not require any special equipment.

Repair Condition	
Crack width	Less than 0.3 mm
Crack Condition	Oil Wet, Oil Water Leakage



Power Healing L300, L400 & L500 for Oily Water Leakage Cracks



Package

Product	One Unit	Main Components
L-300	20kg/container	Inorganic silicate with oil absorber
L-400	20kg/container	Inorganic Salt
L-500	20kg/container	Oil cleaner and bonding agent

Application Procedure

Use L500 to clean the oil-contaminated cracks.



Inject L300 to absorb the remaining oil in cracks, and then L400 is injected for crack filling.



Clean the surface after one day's curing and finish the repair.

Note: When the crack width is large, the crack needs to be repaired using PowerRepair-AO (Special Oil Absorption Patching Mortar)



- After long storage, liquid sedimentation may occur, but there is no problem with performance.
- Do not drink because it is an inorganic silicate-based liquid. If accidentally ingested, seek medical advice immediately.
- If it gets on your skin or eyes, wash it immediately with water and consult a doctor if necessary

Product of

SERIC JAPAN

